Safety Data Sheet

1.0 IDENTIFICATION OF THE SUBSTANCE / MIXTURE

1.1 Product Identification

Substance Kerosene (petroleum)

Commercial Product Name Kerosene

Synonyms Kero, Light heating oil

CAS **8008-20-6**

ECHA Registration No. Greenergy is DU – purchased from within the EU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Specific Use(s) Fuel

Exposure Scenario(s)

Uses Advised Against

Chemical Safety Report

1.3 Details of the supplier of the SDS

Company Greenergy Fuels Limited

Ilona Rose House

Manette St

London W1D 4AL UNITED KINGDOM

Telephone No. **02074047700**

Email <u>msds-info@greenergy.com</u>

1.4 Emergency telephone number

Emergency telephone number +44 (0)1235 836 100

Opening Hours 24 / 7

Version No	2.0	
Last Updated	22 Nov 2016	
Supersedes	1.0	

2.0 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EU) 1272/2008

CLP-Classification: The product is classified as hazardous in accordance with Directive 1272/2008/EEC.

Flam. Liq. 3 H226
Skin Irrit. 2 H315
Asp.Tox. 1 H304
STOT SE 3 H336
Aquatic Chronic 2 H411

For the full text of classification codes and/or H-phrases in this section, see section 2.2 below

2.2 Label elements

Labelling according to Regulation (EU) 1272/2008

CLP pictograms:









GHS02 GHS08

GHS07 GHS09

Signal word: Danger

CLP Hazard statements: H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H304 - May be fatal if swallowed and enters airways.

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects.

CLP Precautionary statements: P301+P310 - If swallowed, immediately call a doctor

P331 - Do NOT induce vomiting
P264 - Wash thoroughly after handling
P273 - Avoid release to the environment

Labelling according to Directives (67/548/EEC - 1999/45/EC)

Not relevant

Other Hazards

Not relevant

3.0 COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

Substance name	Product Identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP / GHS]
Kerosene (petroleum)	CAS no: 8008-20-6 EC no: 232-366-4 EC Index: 649-404-00-4	100	H226 - Flam. Liq. 3 H315 - Skin Irrit. 2 H304 - Asp.Tox. 1 H336 - STOT SE 3 H411 - Aquatic Chronic 2

For the full text of classification codes and/or H-phrases in this section, see section 2.2

3.2 Mixtures

Not applicable

4.0 FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation: Keep at rest

Move to fresh air

Oxygen or artificial respiration if needed

Consult a physician if necessary

Skin contact: Wash off immediately with soap and plenty of water

Take off contaminated clothing and shoes immediately

Wash contaminated clothing before re-use If skin irritation persists, call a physician

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes.

If eye irritation persists, consult a specialist

Ingestion: Do NOT induce vomiting.

Rinse mouth.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: May cause irritation of respiratory tract. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Skin contact: Repeated exposure may cause skin dryness or cracking.

Eye contact: Contact with eyes may cause irritation.

Ingestion: Harmful: may cause lung damage if swallowed. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3 Indication of immediate medical attention and special treatment needed

No data available

5.0 FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Use dry chemical, CO2, water spray or alcohol resistant foam.

Extinguishing media which shall not be used for safety

High volume water jet

reasons:

5.2 Special hazards arising from the substance or mixture

Fire Hazard: Flammable

Specific hazards: Vapours may form explosive mixture with air. Vapours are heavier than air and

may spread along floors. Flash back possible over considerable distance. The pressure in sealed containers can increase under the influence of heat. Cool containers / tanks with water spray. Burning produces noxious and toxic fumes. Possible decomposition products are: COx, H2S, SOx Fire residues and contaminated fire extinguishing water must be disposed of in accordance with

local regulations.

5.3 Advice for firefighters

Special protective equipment for fire-fighters:

Wear personal protective equipment. Wear self-contained breathing apparatus

for firefighting if necessary.

6.0 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: Wear personal protective equipment. Do not breathe vapours or spray mist.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Do not smoke.

6.2 Environmental precautions

Environmental precautions: Do not flush into surface water or sanitary sewer system.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up: Remove all sources of ignition. Do not use tools which may produce sparks.

Prevent further leakage or spillage if safe to do so. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dam up. Sweep up and shovel into suitable containers for disposal. Dispose of in

accordance with local regulations.

7.0 HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling: Wear personal protective equipment. See also section 8. Avoid contact with

skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Do not breathe vapours or spray mist. Ensure

adequate ventilation. Always replace cap after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Do not store near or with any of the incompatible materials listed in section 10.

Store in original container. Keep tightly closed in a dry, cool and well ventilated place. Keep away from open flames, hot surfaces and sources of ignition

7.3 Specific end use(s)

Specific use(s):

8.0 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Component: Kerosene (petroleum) (8008-20-6)

TLV-TWA (mg/m³): 200 (Belgium, Spain); 100 (Poland); 250 (UT4, Krastoff, Germany)

TLV-STEL (mg/m³): 300 (Poland)

DNEL: PNEC:

8.2 Exposure controls

Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment.

Recommended Filter type: A2

Hand protection: Wear chemically resistant gloves tested for breakthrough time for kerosene in

accordance with EN374. The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of

gloves.

Eye protection: Safety glasses (EN 166)

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Wash hands and face before breaks and immediately after handling the product.

Use only in area provided with appropriate exhaust ventilation.



9.0 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance: liquid
Colour: Colourless
Odour: characteristic

рН: no data available Boiling point/boiling range: ca. 140 - 300°C Melting point/range: no data available Flash point: ca. > 38 °C Explosive properties: no data available Oxidizing properties: no data available Evaporation rate: no data available Vapour pressure: 3 kPa @ 20°C Vapour density: no data available

Solubility in water: Insoluble

Viscosity: 1.3 - 2.9 mm²/s @ 20°C Density: 770 - 820 kg/m³ @ 15°C

Partition coefficient: no data available

9.2 Other information

No data available

10.0 STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity: Flammable liquid

See also section 10.5

10.2 Chemical stability

Stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Conditions to avoid: Heat, flames and sparks.

10.5 Incompatible materials

Incompatible materials: Incompatible with strong acids and oxidizing agents. Bases

10.6 Hazardous decomposition products

Hazardous decomposition Burning produces noxious and toxic fumes. Possible decomposition products

products: are: COx, H2S, SOx

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

General Information

Acute toxicity

Component: Kerosene (petroleum) (8008-20-6)

LD50/oral/rat: > 5000 mg/kg

Inhalation: May cause irritation of respiratory tract. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Skin contact: Repeated exposure may cause skin dryness or cracking. Eye contact

Contact with eyes may cause irritation.

Ingestion: Harmful: may cause lung damage if swallowed. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Chronic toxicity:

Further information

No data available

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity effects: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

12.2 Persistence and degradability

Persistence and degradability: No information available

12.3 Bioaccumulative potential

Bioaccumulation: Non-persistent

12.4 Mobility in soil

Mobility: No information available

12.5 Results of PBT and vPvB assessment

Not a PBT or vPvB substance

12.6 Other adverse effects

No data available

13.0 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste from residues / unused products:

In accordance with local and national regulations. Do not burn, or use a cutting torch on, the empty drum. Do not puncture or incinerate.

Codes of waste (2001/573/EC, 75/442/EEC, 91/689/EEC):

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. The following Waste Codes are only suggestions: 130703 – other fuels (including mixtures), 150110 - packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

14.1 UN Number

UN number: 1223

14.2 UN proper shipping name

Proper shipping name: KEROSENE

14.3 Transport hazard class(es)

14.3.1 Overland transport

Class: 3 - Flammable liquids

Danger code: 30 ADR classification code: F1

ADR danger labels: 3 - Flammable liquid



Orange plates:



ADR tunnel restriction code: D/E ADR limited quantities: LQ07 ADR excepted quantities: E1

Inland waterway transport (ADN/ADNR)

ADNR class: 3

14.3.2 Transport by sea

Class: 3 - Flammable liquids

EmS: F-E, S-E

14.3.3 Air transport

Class: 3 - Flammable liquids



14.4 Packing group

Packing group: III

14.5 Environmental hazards

Marine pollutant:



Other information (transport) : No supplementary information available.

14.6 Special precautions for users

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

15.0 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU-Regulations

No data available

15.1. National regulations

WGK:

15.2 Chemical Safety Assessment

Chemical Safety assessment: No data available

16.0 OTHER INFORMATION

Updated sections: All sections reviewed and re-formatted

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.